



NON-SLIP PAVING PAINT

Technical
Data
Sheet

DESCRIPTION

Non-Slip Paving Paint is a hard wearing, flexible water based texture coating specifically designed for surfaces that require extra grip/traction. This Paving paint meets P5 classification (AS 4586-2013)

RECOMMENDED USES

Plain concrete, ramps, pool surrounds, stadium concourses, hallways, pathways, stairs.

FEATURES

Ready for use, pre tinted

No dust inhalation from mixing

Easy to use

Durable







Hard Wearing

Slip Resistant P5 Rating

PROPERTIES

Colour	Various
Gloss	Low Sheen
Pack Sizes	20 Kg
Abrasion Resistance	Very Good
Chemical Resistance	N/A
Solvent Resistance	N/A
Clean Up	Water
VOC (g/L)	<90g/L
Thinner	Water

PERSONAL PROTECTIVE EQUIPMENT

Foot Protection	Eye Protection	Hand Protection	Body Protection	Hearing Protection	Face Protection
					



NON-SLIP PAVING PAINT

Technical
Data
Sheet

COVERAGE

	Minimum	Maximum	Typical
Theoretical Spread Rate (m ² /Kg)	1.5	3	2
Wet Film Thickness (µm)	400	200	300
Dry Film Thickness (µm)	250	120	180

DRY TIMES *

Substrate Temperature	10°C	20°C	30°C
Surface Dry (hours)	6	4	2
Hard Dry (hours)	24	18	12
Recoat Time (hours)	24	18	12

**Drying times are generally related to air circulation, temperature, and film thickness. The figures given above are typical with good ventilation, typical film thickness and single coat application. High humidity condition will lead to longer drying times.*

SURFACE PREPARATION

New concrete surfaces should be allowed to cure for 28 days. Surface should be free of grease, oil, dirt, efflorescence, laitance and paint. Heavily contaminated surfaces should be degreased. Concrete surfaces should be profiled to resemble ICRI CSP 2-3, most easily achieved using mechanical grinding equipment or water blasting (3000psi with a rotary head). Ensure surface is clean, dry and dust free after profiling. Any cracks should be repaired using Crack Repair, please consult TDS for application details.

To get even coverage and to prevent sink back it is strongly recommended to apply Aqua PrimeSeal prior to application, please consult TDS for application.

PROTECT

Non-Slip Paving Paint is best applied by roller or low pressure hopper gun.

Protect the final coat from rain/dew/moisture for at least 24 hours after finishing. Foot traffic is allowed after 24 hours, and vehicles after 5 days. These times will be longer in cooler weather.

PRESERVE

It is recommended to apply a clear coating to protect the colour and make it easier to clean. For pedestrian areas you could use Water-based Concrete Sealer, please consult relevant TDS for application details. For high traffic/vehicles you could use Two pack Water based Polyurethane, please consult relevant TDS for application details.

To ensure the best lifespan it is recommended to sweep, vacuum, or blow the floor regularly to remove dirt and grit. Prompt removal of any spills (e.g., oils and greases) will slow damage of the clear coat.

Use detergents to mop the surface clean as harsh cleaning products can scratch the surface.

Textured surfaces will hold dirt and may require more regular cleaning.

The expected lifespan of any coating is dependent on the location, weather, and traffic the surface is subjected to.



NON-SLIP PAVING PAINT

Technical
Data
Sheet

LIMITATIONS

Non-Slip Paving Paint will make it harder to clean the surface as it holds more dirt. Applying a clear sealer on top of Non-Slip Paving paint will reduce the Slip resistant rating of the Paving paint.

Do not apply if the air or surface temperature is below 10°C, or if the temperature is likely to drop below 10°C during the application and curing process.

Do not apply if the substrate is subject to hydrostatic pressure or rising damp.

Do not apply if the air or surface temperature is above 35°C, or if the temperature is likely to exceed 35°C during the application and curing process.

Do not apply if the relative humidity is greater than or equal to 70%

GENERAL PRECAUTIONS

Do not apply if substrate or surface is likely to be subjected to rain or moisture. Protect the surface against any water impact or moisture after application.

Protect surrounding areas from overspray or product run off.

PRECAUTIONS

Keep out of reach of Children. This product is Non Flammable, Non-Hazardous and Non Dangerous.

Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols. Do not dispose unwanted paint in drain. Check with local council for safe disposal.

PRODUCT COMPATIBILITY

Do NOT mix or use this product in combination with any products not listed in this Technical Data Sheet. The applicator holds full responsibility if other products not listed on this TDS, or similar products of a different brand are used.

USER RESPONSIBILITY

Betu Group warrant that manufactured products are free from defects along with being suitable for the purpose it is intended to be used for as long as it is applied in accordance with the most current TDS from Betu Group.

Differences in substrates, materials and site conditions will require assessment of product suitability for the intended purpose.

The user is responsible for ensuring the suitability of the product for their intended purpose.

STORAGE

Store in a dry area, away from direct sunlight and frost.

Store between 10°C and 30°C

Ensure part used products are correctly sealed. Part used products should be checked to ensure suitability for use.



NON-SLIP PAVING PAINT

Technical
Data
Sheet

FIRST AID

CAUTION: KEEP OUT OF REACH OF CHILDREN

IF ON SKIN: Remove immediately all contaminated clothing and thoroughly wash skin.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF IN EYES: Hold eye open and rinse cautiously with water for at least 15 minutes then immediately see a doctor.

Immediately call a POISON CENTRE (Australia - 13 11 26) or doctor/physician. If skin irritation occurs get medical advice/attention

DISCLAIMER

Industry standards recommend the accurate recording of times and dates, batch numbers, consumption rates and environmental conditions including substrate and air temperatures, humidity levels and dew point readings during both the application and curing processes. Full material warranties cannot be provided unless all the relevant data has been recorded accurately. The technical information and application advice given here is based on the best information available at the time of print. As the information herein is of a general nature, no assumption can be made as to the products suitability for a particular use or application. Field support, where provided, does NOT constitute supervisory responsibility. Suggestions made by Betu Group either verbally or in writing may be followed, modified, or rejected by the owner, engineer or contractor since they are responsible for carrying out procedures appropriate to a specific application. If in doubt contact Betu Group technical department for advice.